

## Технические характеристики:

<b>Input</b>	4 DVB-C/T/T2/S/S2 Tuner (Optional) and 2 ASI input				
<b>Tuner Section</b>	DVB-C	Standard	J.83A(DVB-C), J.83B, J.83C		
		Input Frequency	30MHz-1000Mhz		
		Constellation	16/32/64/128/256 QAM		
	DVB-T/T2	Input Frequency	30MHz-999.999Mhz		
		Bandwidth	6/7/8M bandwidth		
	DVB-S	Input Frequency	950-2150MHz		
		Symbol rate	2-45Msps		
		Signal Strength	-65~-25dBm		
		FEC Demodulation	1/2, 2/3, 3/4, 5/6, 7/8 QPSK		
	DVB-S2	Input Frequency	950-2150MHz		
		Symbol rate	QPSK 1~45Mbauds 8PSK 2~30Mbauds		
		Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10		
Demodulation Mode		QPSK, 8PSK			
<b>Multiplexing</b>	Maximum PID Remapping	128per input channel			
	Function	PID remapping (automatically or manually)			
		Accurate PCR adjusting			
<b>Modulation</b>	DVB-C	Standard	J.83A(DVB-C), J.83B, J.83C		
		MER	≥40dB		
		RF frequency	30~999MHz, 1KHz step		
		RF output level	-20~0dbm(87~107 dbμV),0.1db step		
		Symbol rate	5.0Msps-9.0Msps, 1ksps stepping		
		RF Out	4*DVB-C carriers output		
			J.83A	J.83B	J.83C
		Constellation	16/32/64/128 /256QAM	64/256 QAM	64/256 QAM
		Bandwidth	8M	6M	6M

	DVB-T	Bandwidth	6M, 7M, 8M
		Constellation	QPSK, 16QAM, 64QAM
		Code rate	1/2, 2/3, 3/4, 5/6, 7/8
		Guard Interval	1/32, 1/16, 1/8, 1/4
		Transmission Mode:	2K, 8K
		MER	≥40dB
		RF frequency	30~999MHz, 1KHz step
		RF Out	2*DVB-T carriers output
		RF output level	-20~0dbm(87~107 db μV),0.1db step
<b>System</b>	Local interface	LCD + control buttons	
	Remote management	Web NMS	
	Stream Out	2 ASI out(BNC type)	
		IP (2*MPTS over UDP) out (RJ45, 1000M)	
	Language	English and Chinese	
Upgrading	Web and USB		
<b>General</b>	Dimension	482mm×300mm×44.5mm(W*D*H)	
	Weight	3.7kg	
	Temperature	0~45°C (Operation) ; -20~80°C (Storage)	
	Power	AC 100V ±10%/60Hz; AC 220V ±10%, 50/60HZ	
	Consumption	25W	